Bravura

TELLURIDE

Specifications: ANSI Rated Grade 2


Door Prep	Deadbolt cross bore: 2-1/8" Handleset cross bore: 2-1/8" Edge bore: 1" Latch Face: 1" x 2-1/4" Mounting (center to center) 5-1/2"	Latches	2-3/8 Mortise Latch Standard 2-3/4" Mortise Latch or Drive-In Latch Available
		Cylinder	SC1 5-Pin C Keyway
Door Thickness	1-3/4" Standard, must specify 1-3/8" 2", 2-1/4", & 2-1/2" Extention Kits Available	Strikes	Deadbolt: Full lip round corner (9117 & 9113) Handle: Full lip round corner (9103)
Interconnected	1-Pc Full Plate - Standard 2-Pc Sectional - Not Available	Door Handing	Specify handing when ordering lever as Interior option

TELLURIDE 695 & 692 ESCUTCHEON SIZE IS 9-5/16" X 2-5/8"





US10B, US15, US26




Functions:
Single Keyed
Passage/Privacy
Half Dummy
Full Dummy

TELLURIDE 696 ESCUTCHEON SIZE IS 10-1/2" X 3-1/8"







Functions:
Single Keyed
Passage/Privacy
Half Dummy
Full Dummy

HOW TO ORDER TELLURIDE LOCKS

